

## 太陽能電池片

單/多晶	單晶	多晶	
尺寸	156 x 156mm	156 x 156mm	156 x 156mm
尺寸公差	± 0.5mm	± 0.5mm	± 0.5mm
對角線差	200mm ± 0.5mm (round chamfers)		
厚度	180~200μm	180~200μm	180~200μm
厚度公差	± 30μm	± 30μm	± 30μm
正面規格	Acid or alkaline textured surface with SiNx anti-reflecting coating. Color: Blue, Dark Blue and Indigo Negative Pole(-)		
正面 Busbar	2 Busbars	3 Busbars	2 Busbars
正面 Busbar 寬度	2.0mm± 0.1mm	1.5mm± 0.1mm	2.0mm± 0.1mm
正面 Busbar 間距	75mm	52mm	75mm
背面規格	Aluminum back surface field Positive Pole(+)		
背面 Busbar 寬度	4.0mm ± 0.1mm	3.0mm± 0.1mm	4.0mm ± 0.1mm
效率範圍	18.2~19.8	17.2~18.3	17.0~18.1
溫度係數	Isc: 0.03%/°C Voc:-0.38%/°C FF:-0.122%/°C Power:-0.46%/°C	Isc: 0.05%/°C Voc:-0.34%/°C FF:-0.140%/°C Power:-0.43%/°C	Isc: 0.05%/°C Voc:-0.34%/°C FF:-0.140%/°C Power:-0.43%/°C